

- Fixture uses high intensity LED's in a variety of color combinations.
- Compact, rugged, linear fixture easily integrates into many applications.
- Many options in optics, color temperature and accessories.
- Wireless DMX controllable - WA5 required for wireless transmission.
- Simple installation process using conventional wiring.
- UL Listed for dry or damp or wet location (model dependent).
- Clear anodized aluminum housing with a durable finish ensuring it is weather and abrasion resistant.
- Clear or Diffuse (interior only) lens.
- Uses any standard DMX 512 show controls.
- Contact Boca Flasher for tips with custom installations.




PRODUCT SPECIFICATIONS:


COLOR OPTION	OPTIC	VOLTAGE	FINISH	LOCATION	MOUNTING	WHITE MIXING OPTIONS
HPFB			A			
RGB	10°	120V	A Clear Anodized Aluminum	I Interior-IP60 E Exterior-IP65 W Wet-IP68	F Fixed S Swivel V Vandal Resistant	If specifying RGBW indicate white options here: (Up to 3 different options can be specified) 2700K 3000K 3500K 4000K 5000K Amber
RGBW color & white (See Options)	30°	277V				
RGB/WWW	60°					
RGB/WWW	10°x 60°					
RGB/WWA	30°x 60°					
LENS	CONTROLS	HEXCELL				
C Clear	3 3 Channel DMX	Y Yes				
D Diffused (Interior Use Only)	4 4 Channel DMX 6 6 Channel DMX 8 8 Channel DMX	N No				

DIMENSIONS:


Plan View



Elevation View



End View



HPFB


Medium Profile Color Changing LED Fixture

TECHNICAL SPECIFICATIONS:

WATTAGE	32 watts per linear ft.*
INPUT VOLTAGE	120 VAC or 277 VAC
CONTROL	Standard DMX 512
LED SPACING	1.0" on center
LENGTH	1 ft., 2 ft., or 4 ft.
TOTAL HEIGHT	2.51" (not including clip)
TOTAL WIDTH	4.19"
COLOR OPTIONS	RGB, RGBW
MOUNTING	Fixed, Swivel, or Vandal Resistant
AVAILABLE OPTICS	10°, 30°, 60°, 10° x 60°, 30° x 60°
RATING	IP60, IP65, IP68
COLOR RENDERING INDEX (CRI)	90+ for White Mixing Only
POWER CABLE	UL Standard 10 ft.
ENVIRONMENTAL	Operating temperature--40°F-140°F Ambient(-40°C-60°C)** Storage temperature -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

MOUNTING INFORMATION:

- For vertical installation please contact the factory for specific mounting instructions.
- For installations above 4' please contact the factory.



*Custom wattage available upon request.

Title 24 compliant fixture not to exceed 18 watts / 4ft fixture.

** Military spec available under special request-lead times may be impacted.