



### TECHNICAL DATA

Wattage	8 watts per linear ft.
Input Voltage	12VAC
Input Current	410mA RMS per linear foot
Control	Standard Magnetic Low Voltage Dimming
Power Cable Length	UL Standard 6ft
LED Spacing, per strip	1.5" on center
Fixture Length	15"-99", in 6" increments
Fixture Width	2.36"
Total Diameter (not including clip)	1.50"
Mounting	Fixed Clip
Available Optics	10°, 30°, 60°, 10°x60°, 30°x60°, 120°
Housing	Underwater Polycarbonate Tube
Color Options	27K, 3K, 35K, 4K, 5K, amber, r, g, b
Color Rendering Index (CRI)	+90 CRI
Ratings	IP68
Total linear ft per 20A breaker	160 feet
Total linear ft per 15A breaker:	120 feet
Total linear ft per power feed	10 feet
Transformer	Primary 120V or 277V, Secondary 12V

LED Lighting Systems, Technologies & Manufacturing

552 N.W. 77TH ST  
BOCA RATON, FL 33487

www.bocafletcher.com  
(561) 989-5338

THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHTS OF BOCA FLASHER INC.

## HP-SUBMERSIBLE

FILE NAME: TECHNICAL SHEET	PART #: HP-SUB
DRAWN BY: STEPHANIE BURKE	03 / 16 / 15
DESIGN BY: DAVE URBAN	
APPROVED BY: STEPHANIE BURKE	
SCALE: NTS	SHEET: 1 OF 1