

# **NICHE-HV**Micro Profile LED Fixture Line Light

Customer: Date: Type:

Project:



- · Compact, variable light fixture for interior use
- · Fixture comes in 12" increments.
- · Many options in color temperature to suit a range of projects. Call factory for additional options.
- $\cdot$  Boca Flasher's patented CleanDim® technology ensures even dimming from 0-100%.
- · Fixtures are compatible with both forward and reverse phase dimming or can use Boca's SDS module for 0-10V, DALI or DMX Dimming.
- · Uses standard line voltage dimming in forward or reverse phase.
- · Linkable for longer runs.
- · Interior installation use only.












## **PRODUCT SPECIFICATIONS:**

		WATTAGE	COLOR OPTION	OPTIC	VOLTAGE	FINISH	LENS	MOUNTING
Niche	HV			120°	120V	А		F
		4W 8W	2400K 2700K 3000K 3500K 4000K 5000K			A Clear Anodized Aluminum	C Clear CLD Clear Light Diffused HD Heavy Diffused	<b>F</b> Fixed

### **DIMENSIONS:**

Plan View Elevation View





# **NICHE-HV**

Micro Profile LED Fixture Line Light




## **TECHNICAL SPECIFICATIONS:**

WATTAGE	4 or 8 watts per linear ft.					
INPUT VOLTAGE	120VAC					
CONTROL	Leading Edge/Trailing Edge line dimmer 0-10V, DALI, or DMX*					
LED SPACING	5/8" on center					
LENGTH	12"-72" in 12" increments, allow 1/4" for each end cap and 2" for power feed cable					
TOTAL HEIGHT	0.97" (not including clip)					
TOTAL WIDTH	0.98"					
COLOR OPTIONS	2400K, 2700K, 3000K, 3500K, 4000K, 5000K					
MOUNTING	Fixed					
AVAILABLE OPTICS	120°					
RATING	Interior Only					
COLOR RENDERING INDEX (CRI)	90 + CRI					
POWER CABLE	UL Standard 10 ft.					
Operating temperature40°F-140°F Ambient (-40°C-60°C)						

**MOUNTING INFORMATION:** 

- For vertical installation please contact the factory for specific mounting instructions.
- · For installations above 4' please contact the factory.



#### **LUMINAIRE INFORMATION:**

IES Files Pending

· Specific Files Available On Request

**ENVIRONMENTAL** Storage temperature -40°F-140°F Ambient indoor fixtures

operation limited to =<50% relative humidity

<sup>\*</sup>Uses Boca SDS Module for 0-10V, Dali, or DMX Dimming.

<sup>\*</sup> Military spec available under special request-lead times may be impacted.